



A.J. World Co., Ltd.  
16, Magokjungang 14-ro, Gangseo-gu, Seoul, 07789, Republic of Korea  
Tel. +82-2-567-5216 Fax. +82-2-563-2433

Factory in Vietnam - SCON Co., Ltd.  
No. 6 VSIP II-A, Street 29, VSIP II-A Vinh Tan Ward, Tan Uyen Town, Binh Duong Province, Vietnam  
Tel. +84-274-222-2075~77 Fax. +84-274-222-2083

# Test Report

Client : Trung Kien Ha Nam Co., Ltd.  
Address : 416/16A Pham Van Bach Street, Ward 15, Tan Binh District, Ho Chi Minh City, Vietnam

Tested Sample(s) :

No.	Item
1	FAOC-VF-SC/APC (AJW-FAOC-VF-SC/APC)

Test Results :

Category	Requirements	Results	
		PASS	FAIL
Appearance	No mechanical damage	o	
Dimension	54 x 9 x 8.3 (mm)	o	
Connector Type	TIA/EIA 604-3(SC), APC - Green	o	
3-Way Cable Locking	0.125mm, 0.25mm, Cable 2x3	o	
Boot	Folding Type	o	
Matching Gel	Origin : USA	o	
Package	FAOC-VF unit, cleaning cloth, installation guide and FAOC-VF multi-functional jig (Jig is provided for every 10 connectors.)	o	
Operation Conditions	-40°C ~ +75°C, < 95%RH	o	

Category	Test Methods	Conditions	Test Standards	Results	
				PASS	FAIL
Insertion Loss	IEC 61300-3-34	-	$\leq 0.3\text{dB}$	o	
Return Loss	IEC 61300-3-6	-	$\geq 55\text{dB}$ (APC)	o	
Endface Geometry	GR-326-CORE SEC 4.4.5	-	Radius of curvature : 5~12mm Apex offset : < 50um Fiber height : -50~+50nm	o	
Tension	IEC 61300-2-4	$\geq 30\text{N}$	$\Delta\text{IL} \leq 0.2\text{dB}$ , No mechanical damage	o	
Repeated Connection	IEC 61300-3-34 / IEC 61300-3-6	$\geq 5$ times	$\text{IL} \leq 0.3\text{dB}$ , No mechanical damage	o	
Repeated Connection	IEC 61300-3-34 / IEC 61300-3-6	$\geq 10$ times	$\text{IL} \leq 0.5\text{dB}$ , No mechanical damage	o	
Repeated Connection (Adapter)	IEC 61300-2-2	> 500 times	$\Delta\text{IL} \leq 0.2\text{dB}$ , No mechanical damage	o	

