

FAOC

AJW FAOC is designed to manage fast, easy and stable on-site fiber connections with unique V-groove technology. The cable clamping method offers stable cable retention and installer convenience. It reduces connection defect rate by allowing re-assembling multiple times in the field without additional tool. It accommodates 0.25 mm, 0.9 mm, 2.0 mm, 2x3 mm (flat), and 3.0 mm (round) cable.

Specifications

Model	SS57A	SS54A	SS50A	LS40A	FS55A	SL54A
Product				· ·		
Dimension (mm) L x W x H	57 x 9 x 9	54 x 9.1 x 9.1	50 x 9.2 x 9.2	40 x 5.7 x 6.1	55 x 9.8 x 9.8	54 x 9 x 8.5
Connector Type	SC LC FC				SC	
Ferrule Type	UPC, APC					
Fiber Type	SM, MM(OM1, 2, 3)					
Accommodating Cable						2x3mm (Flat Cable)
Cable Clamp	3-Leg 2-Leg Cable Clamp Folding Cable Clamp				N/A	
Boot Type						Sliding Type Boot
Insertion Loss	≤ 0.3dB					
Return Loss	UPC: ≥ 45dB, APC: ≥ 55dB					
Fiber Length (Ø0.25mm)	241	mm	18mm	14mm	20	mm
Fiber Length (Ø0.125 mm)	10mm					

All components are compliant with EU RoHS Directive (2011/65/EU amended by 2015/863).





FAOC (Screw Type Boot)


SS54A

SC Connector (54mm Body) with 2-Leg Cable Clamp



Structure










FAOC (Screw Type Boot)


SS57A

SC Connector (57 mm Body) with 3-Leg Cable Clamp



SS50A

SC Connector (50 mm Body) with Folding Cable Clamp









FAOC (Screw Type Boot)

LS40A

LC Connector (40mm Body) with Folding Cable Clamp









FS55A

FC Connector (55mm Body) with Folding Cable Clamp









FAOC (Sliding Type Boot)

SL54A

SC Connector (54 mm Body) with Sliding Type Boot



Sliding Cable Locking Structure

